

AkzoNobel

AkzoNobel SolidoColor SC-T470

Premium quality with improved performance

Pigmented topcoat system










AkzoNobel SolidoColor SC-T470

Pigmented topcoat system

AkzoNobel SolidoColor SC-T470 is a two-pack, solventborne, premium quality, pigmented topcoat system. Based on PU alkyd technology with low yellowing hardener, this system can be used to produce a wide color range with RAL, NCS and Sikkens 5051 color collections.

Key benefits:

- 
Sag resistance:
 High sag resistance to allow for vertical application
- 
Scratch resistance:
 Excellent scratch resistance for extra durability
- 
Fast drying:
 Fast drying - transportable after 12 hours
- 
Optional gloss levels:
 Different gloss levels available allowing for customised aesthetics
- 
Compatible:
 Compatible with PU tinting systems to create a wide variety of colours
- 
Color characteristics:
 Improved color characteristics - color accuracy, better database, software and spectro connection
- 
Performance:
 Overall improved performance when compared to previous formulations



www.akzonobel.com

We've been pioneering a world of possibilities to bring surfaces to life for well over 200 years. As experts in making coatings, there's a good chance you're only ever a few meters away from one of our products. Our world class portfolio of brands – including Dulux, International, Sikkens and Interpon – is trusted by customers around the globe. We're active in more than 150 countries and have set our sights on becoming the global industry leader. It's what you'd expect from the most sustainable paints company, which has been inventing the future for more than two centuries.

For more information please visit www.akzonobel-woodcoatings.com.

© 2021 Akzo Nobel N.V. All rights reserved

Product details:

Color: Pigmented

Gloss grade*:

- 30/Colour semi gloss
- 20/Colour semi matt
- 10/Colour matt

*(60°C Gloss meter)

Application: Furniture, cabinets and interior doors

Substrate: Applicable to almost all wood types

Application method: Spray



Contact Us:

For more information on our featured products, please contact your local representatives.